

4

3

2

DWG NO. 1 2220000158.PDF

These drawings and specifications are the property of Interconnect Systems, LLC, and shall not be reproduced, or copied, or used without prior written permission.

REVISION HISTORY

REV	DESCRIPTION	ECN	DATE	APRV'D
1	INITIAL RELEASE	--	05/10/18	RF

D

DEVICE SIDE

Pointing Accuracy: ± 0.095 mmSpring Force: $\pm 25\%$

STATE	TRAVEL	SPRING FORCE
Initial Travel	--	4.6g (0.162oz)
Recommended Travel	0.96mm (0.0378")	33.0g (1.164oz)
Full Travel	1.30mm (0.0512")	43.1g (1.520oz)


PART	MATERIAL	FINISH
Plunger [Device]	Hardened Beryllium Copper	Gold Plated
Plunger [Board]	Hardened Beryllium Copper	Gold Plated
Barrel	Phosphor Bronze	Gold Plated
Spring	Stainless Steel	Gold Plated

Notice:**Pointing Accuracy needs to be considered in the housing design due to possible shorting or abnormal mechanical operation.**

B

A

BOARD SIDE

CONTRACT NO. SO28394				INTERCONNECT SYSTEMS INTL, LLC a molex company 741 FLYNN ROAD, CAMARILLO, CALIFORNIA 93012	
DRAWN BY R. FLORES	DATE 02/08/18	TITLE POGO PIN 0.65mm Pitch, H/H Plungers, 33.0g SF, Au Plate Finish			
DESIGNER ET	DATE 02/08/18				
CHECKER J. GELACIO	DATE 05/10/18				
QA N/A	DATE	SIZE A	RoHS	SCALE N/A	DRAWING NO. 2220000158.PDF
PROCESS ENG. N/A	DATE	SAVED AS: 2220000158.PDF	FINISHED ASSY: --	REV 1	SHEET 1 OF 1

4

3

2

1

↑