
(	Catalog Pa	ge 197-1		Hi Temperature Plastic			
	.100	HDD	40 + 4 Female HD connector -	Surface			
	.100	прр	surface mount	Mount			

ATA Disk Drive Combo Conn: 40 Female + 4 Female Power - Surface Mount



Base Part	А		В		С		D		Е		Plating	Number of
Number	mm	Inch	<b>Options</b>	Postions								
7566											Х	One Per
<b>7566HS</b> Hot Swap											Х	One Per

Technical Notes				
Mates with Drives from:	Seagate - IBM - Quantum (see Maxtor model list)- Fujitsu - Samsung			
Insulation Material:	Glass Filled Nylon 46 - UL 94V-0 rated - Black (std)			
Insulation Resistance:	5000 MegOhm @ 500VDC			
Plating:	Power = tin : Signal = $G2LF$ (gold/ tin)			
Max Processing Temp:	250°C for 60 seconds			
Insertion Force:	11 pounds (5.0 kg) total			
Extraction Force:	6.8 pounds (3.0 kg) total			
Plastic:	High Temperature Plastic			

## INTERCONNECT SYSTEMS INC.

741 Flynn Road, Camarillo, Ca 93012 · (805) 482-2870 · fax (805) 482-8470 · e-mail:<u>info@isipkg.com</u>