

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND IS THE PROPERTY OF INTERCONNECT SYSTEMS INTL, LLC. IT SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED TO THIRD PARTIES WITHOUT PRIOR WRITTEN CONSENT OF INTERCONNECT SYSTEMS INTL.



REVISION HISTORY

REV	DESCRIPTION	ECN	DATE	APRVD
1	INITIAL RELEASE	--	10/23/23	ET


D

C

B

A

TOP PLUNGER



BOTTOM PLUNGER

Pointing Accuracy:  $\pm 0.04$  mm

Spring Force:  $\pm 20\%$

STATE	TRAVEL	SPRING FORCE
Initial Travel	--	4.0g (0.141 oz)
Recommended Travel	0.35mm (0.0138")	12.8g (0.451 oz)
Full Travel	0.45mm (0.0177")	15.3g (0.540 oz)

PART	MATERIAL	FINISH
Spring	Music Wire	Gold Plated
Barrel	Ni-Au Alloy	Gold Plated
Top Plunger	Hardened Beryllium Copper	Gold Plated
Bottom Plunger	Hardened Beryllium Copper	Gold Plated

**\*NOTE:** It is important to verify the working travel of the probe when designing the fixture or socket. The recommended working travel is 0.35mm and there is only a difference of 0.10mm to full compression. Full compression may cause the pin to fail and damage the device, spring, plungers and/or PCB pads.

CONTRACT NO. 129906758				<b>INTERCONNECT SYSTEMS INTL, LLC</b> a molex company	
CAGE CODE 3F8U4		741 FLYNN ROAD, CAMARILLO, CALIFORNIA 93012 805-482-2870 MAIN   805-482-8470 FAX			
PREPARED BY R.FLORES	DATE 10/23/23	TITLE POGO PIN 0.30mm Pitch, C/E Plungers, 12.8g SF, Au Plate Finish			
DESIGNER ET	DATE 10/23/23				
CHECKER ET	DATE 10/23/23				
QA --	DATE --	SIZE A	ROHS YES	SCALE N/A	DRAWING NO. POGO-PIN-2.40-3
PROCESS ENG. --	DATE --	SAVED AS: POGO-PIN-2.40-3.PDF		FINISHED ASSY: --	MOLEX PART NUMBER 2220000807
					REV 1
					SHEET 1 OF 1

4

3

2

1