

REV	DESCRIPTION	DATE	BY
A	NEW DRAWING	02/08/05	M.W.

SKT2225

Applications


EMULATION probes are used in battery charger or electronic device applications such as:

1. Camcorders
2. Circuit board to board docking stations
3. Cellular Phones
4. 2-way radios
5. Computer docking stations
6. Cordless phones
7. Chargers
8. InkJet Printers
9. Notebook and laptop computers
10. AC/DC power supplies

Benefits and Features:

1. Low resistance (average 16 milliohms)
2. Better contact than nickel-plated strip contacts
3. Maintains high compliancy
4. Less susceptible to damage
5. Can accommodate up to .025" subsurface battery mating contact
6. Longer life than conventional interconnects

Notes: Consult factory for higher temperature applications.



Probe Specifications		
Mechanical		
Full Travel:	.110 (2.79)	
Recommended Travel:	.060 (1.52)	
Mechanical Life Exceeds:	250 x10 ⁶ cycles	
Operating Temperature: -55°C to +85°C Consult factory for other temperature requirements.		
Electrical (Static Conditions)	5 amps d.c. max Maximum Current Rating (Non-inductive DC)	
Average Probe Resistance	30 mΩ	
Materials and Finishes		
Plunger:	Hard nickel over beryllium copper, gold plated	
Barrel:	Gold plated Hard nickel over brass	
Spring:	Standard: Beryllium copper, silver plated Alternate: Music wire	
Mounting Hole Size:	.043 (1.09) min	
Spring Force in oz. (grams)		
Spring Type	Preload	Recommended Travel
Standard	0.40 (11.35)	1.14 (32.35)
Alternate	1.0 (28.38)	3.0 (85.13)
Tip Styles	B	
Termination		

Length	13.0mm	Plunger D
Pitch	2.65mm	(Single Plunger)

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED



Emulation Technology, Inc.

VLSI and SMT ADAPTERS and ACCESSORIES

2344 Walsh Avenue, Bldg F
Santa Clara, CA 95051

TEL: (408) 982-0660
FAX: (408) 982-0664

SHEET: 1 OF 1	DATE: 2/08/05	REVISION:	ASSEMBLY DRAWING
CHECKED: Perry Munroe	DRAWN: Mark Wilson	ITEM: POGO-PIN-13.0-1	
DO NOT SCALE DRAWING			DESCRIPTION: POGO-PIN-13.0-1